

# enviro prime WB

## Water Based Acrylic Primer



Date: Jan 09  
Issue: 3

### Description

Enviro Prime WB is a 1-Part water based acrylic primer. It provides excellent adhesion for most of the Enviro range of systems.

### Advantages

Primer/sealer for concrete, brick, tilt up panels and most other masonry. Excellent key coat for plywood, particle board and many other substrates prior to application of Enviro Clad.

### Uses

Enviro Prime WB is suitable for use with the following range of Enviro Systems:

- Enviro Flex
- Enviro Flex 200P
- Enviro Clad

### Physical Properties

• VOC Content	Low	• Colour	White
• Flammability	Non Flammable	• Recoat Time	2 hours
• Dry Time	Dust Free: 30 minutes Hard Dry: 7 days		

### Application Directions

#### Substrate Preparation

The surface must be clean, dry and free from all loose particles including dust, laitance, grease, coatings and curing compounds.

Where boards are used, these are to be fixed according to manufacturer's instructions and are to be fit for purpose.

#### Application

Enviro Prime WB is suitable over the following substrates:

- New Concrete Cured for min. 28 days
- Renders Cured for min. 7 days
- Compressed fibreboards
- Timber
- Plasterboard

One 15 ltr Drum will coat approx 75 – 120m<sup>2</sup>

## Estimating Data (Theoretical)

Enviro Prime WB can be applied using brush, roller or spray. One 15L drum will coat approximately 75-120m<sup>2</sup>. Apply one coat of Enviro Prime WB at a rate of 5-8m<sup>2</sup> per litre.

## Packaging

Enviro Prime WB is supplied in 1 ltr, 4 ltr and 15 ltr plastic pails.

## Drying

Enviro Prime WB generally will dry within 30 minutes depending on weather/substrate.

## Cleaning

Enviro Prime WB should be removed from all tools and equipment, prior to hardening, with water. Cured material can only be removed mechanically.

## Storage

In sealed containers at 5° – 30°C. Do not expose to moisture or direct sunlight.

## Shelf Life

Enviro Prime WB can be stored in its original sealed containers for 12 months in a dry cool storage.

## Safety Advice

Enviro Prime WB is non-toxic; however contents should not be swallowed or inhaled. Wear simple dust masks, goggles and gloves when handling. Wash off splashes of material with clean water. If irritation continues seek medical advice. Refer to MSDS for full safety and handling procedures.

**KEEP OUT OF REACH OF CHILDREN.**



Manufactured by Waterproofing Technologies Pty Ltd  
Address: 295 Princes Highway St Peters NSW 2044 Sydney Australia  
Telephone: +61 2 8595 8699  
Facsimile: +61 2 8595 8660  
Web: [www.envirosystems.com.au](http://www.envirosystems.com.au)

### Statement of Responsibility

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use.

### Note:

Field service where provided, does not constitute supervisory responsibility. Suggestions made by Enviro Systems either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Enviro Systems are responsible for carrying out procedures appropriate to a specific application.