

enviro prime BB

Bitumen Based Primer



Date: Jan 09
Issue: 3

Description

Enviro Prime BB is an industrial bitumen based primer, formulated to adhere to damp surfaces and used for priming suitable substrates for the application of Enviro Imper torch on membrane.

Advantages

- Adheres to damp surfaces
- Ease of use
- Single pack
- Can be used as a protective coating

Uses

Enviro Prime BB is recommended as the priming coat for Enviro Imper torch on membrane. Enviro Prime BB can also be used to protect metal surfaces against oxidization from water, sunlight, and weather exposure.

Physical Properties

- | | | | |
|---------------|--|-----------------|--|
| • Colour | Black | • Material | Bitumen, Solvents |
| • Odour | Bitumen, Solvents | • Coverage Rate | Approximately 10m ² per litre |
| • Drying Time | Touch Dry – 2 to 4 hours depending on ambient temperature
Full Cure – 24 hours depending on ambient temperature | | |

Application Directions

Surface Preparation

The surface must be clean, dry and free from all loose particles including dust, laitance, grease, coatings, curing compounds and any other foreign matter.

New hot dip galvanizing must be weathered for a minimum of 6 months before the application of Enviro Prime BB.

Application

Apply one coat of Enviro Prime BB by brush, spray or roller. Allow to cure for 24 hours before the application of Enviro Imper torch on membrane.

Note: Enviro Imper should be applied over Enviro Prime BB within 48 hours of curing.

Packaging

20 ltr and 205 ltr drums

Cleaning

Enviro Prime BB should be removed from all tools and equipment, prior to hardening with Enviro Thinners No.1. Observe all OH&S and MSDS information pertaining to safe usage and handling of solvents. Cured material can only be removed mechanically.

Storage

In sealed containers at 5° – 30°C. Do not expose to moisture or direct sunlight.

Shelf Life

Enviro Prime BB can be stored in its original sealed containers for 12 months in controlled environments.

Safety Advice

When using Enviro Prime BB always provide adequate ventilation and wear appropriate Personal Protection Equipment (PPE) during use. Avoid contact with skin. Avoid breathing vapours. Wear protective eyewear. If inhalation effects occur, remove to fresh air. If discomfort persists or any breathing difficulty occurs or if swallowed, seek medical attention. Refer to MSDS.

KEEP OUT OF REACH OF CHILDREN.



Manufactured by Waterproofing Technologies Pty Ltd

Address: 295 Princes Highway St Peters NSW 2044 Sydney Australia

Telephone: +61 2 8595 8699

Facsimile: +61 2 8595 8660

Web: www.envirosystems.com.au

Statement of Responsibility

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, his representative or the contractor is responsible for checking the suitability of products for their intended use.

Note:

Field service where provided, does not constitute supervisory responsibility. Suggestions made by Enviro Systems either verbally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not Enviro Systems are responsible for carrying out procedures appropriate to a specific application.